ViewSonic MiewBoard IFP5550-2


Key Features

- Ultra fine touch technology enables real-time response dual-pen writing with a 3mm diameter pen tip
- 2.1 Stereo sound with a built-in woofer
- Built-in myViewBoard[™] whiteboarding software to collaborate on the go
- 4-way split screen content sharing with builtin ViewBoard® Cast software
- SmartPort[™] shared front USB ports for internal & external PCs



Product **Description**

The ViewBoard® IFP50 series embraces ultra fine touch technology to offer fine precision writing. Along with slim IR touch and its optimized integration, the processing time is faster than traditional IR panels. Meanwhile, smooth dual-pen writing with our new, slim 3mm pens enables teachers and students to work efficiently on any detailed tasks that require the accurate use of fine tipped pens during group discussion. On top of that, the ViewBoard® IFP50 series is designed with a slim bezel to broaden your viewing experience, so that even at the edge you can write clearly and thinly. It is also well integrated with myViewBoard™ whiteboarding software to collaborate on the go, and further complimented by ViewBoard® Cast software for 4 way split screen content sharing.





DISPLAY		BUNDLE SOFTWARE	
Panel Size:	55"	Basic Annotation Software:	myViewBoard / vBoard Lite
Type/Tech:	TFT LCD Module with DLED Backlight.	Pro Annotation Software:	myViewBoard for windows (Embedded in Windows Slot-in PC)
Display Area (mm):	1209.6(H) x 680.4 (V) (54.64" diagonal)	Wireless Presentation with Touch Feedback: Viewboard Cast:	yes
Aspect Ratio:	16:9	ViewSonic Launcher:	Embedded
Native Resolution:	UHD 3840x2160(Pixels)	SPECIAL FEATURES	
Colours:	1.07B colours (10bit)	All-in-one USB port (combine Windows/Android USB port; no need to distinguish them	Front "SmartPort™ USB" to all channels.
Brightness:	350 nits (typ.) 300 nits (min.)		
Contrast Ratio:	5000:1 (DCR)	anymore):	
Response Time:	8ms	Simple LAN sharing between IFP and slot-in device:	10M/100M for Android 10M/100M/1000M for slot-in PC
Viewing Angles:	H = 178, V = 178 typ.	POWER	
Backlight Life:	30,000 Hours (Min)	Voltage:	100-240VAC +/- 10% Wide Range
Surface Treatment:	Anti-Glare	Consumption:	81W (Typ.)
Bezel:	Slim		< 0.5 W ("Off")
Orientation:	Landscape	ERGONOMICS	400 000
PLATFORM		Wall Mount (VESA®):	400 x 200
Processor:	ARM Cortex A73 dual-core 1.2GHz		0°C to 40°C
RAM:	2GB DDR4	Temperature (° C):	
Storage:	16GB		10% ~ 90% RH non-condensing
тоисн		DIMENSIONS (W X H X D)	49.9 x 30.4 x 3.3 in / 1268 x 773 x 85
Type/ Tech:	IR Recognition	Physical (inch / mm):	49.9 X 30.4 X 3.3 In / 1268 X 773 X 85 mm
Touch Resolution:	32767 x 32767	Packaging (inch / mm):	56.2 x 34.6 x 8.7 in / 1428 x 878 x
Touch Point:	20 points touch, 10 points writing		220 mm
INPUT		WEIGHT	69 24 lb / 21 Ka
HDMI:	2.0 x3 (3840x2160 @60Hz)	Net (lb / kg):	68.34 lb / 31 Kg
RGB / VGA:	x1	Gross (lb / kg): REGULATIONS	85.98 lb / 39 Kg
Audio:	x1 (PC audio in)	REGULATIONS	FCC, cTUVus, CB, CE, BSMI, RCM,
CVBS:	x1	REGULATIONS:	EAC
RS232:	x1	ENERGY STAR VERSION	
OPS:	x1 PC Slot (proprietary)	Energy Star version:	ES8.0
OUTPUT		EEI RATING	
HDMI:	x1	EEI rating:	A+
Audio:	x1 (Earphone out)	PACKAGE CONTENTS	
SPDIF:	1(optical)		1. Power cable (3 meters) x 4 2. Remote control
RS232:	x1		3.USB cable (3 meters) 4. AV cable
LAN		PACKAGE CONTENTS:	5. Touching pen x 2 6. Quick Start Guide
RJ45:	x1	TROUGE CONTENTS.	7. RS232 adapter 8. Clamp x 5
USB			9. Plate 10. Screw x 8
Туре А:	USB 2.0 x4(including 2 USB port in front) USB 3.0 x2(including 1 USB port in	COMPATIBLE SLOT-IN PC	11. HDMI cable
	front)		VPC14-WP series
Туре В:	x2, for touch	Compatible Slot-in PC:	VPC10-WP series VPC15-WP series
SPEAKERS			VPC16-WP series VPC17-WP series
SPEAKERS:	10W x 2 + 15W x 1		
TOP CAMERA PLATE			
Yes			
	Defecte limit to b		
RGB PC/HDMI PC:	Refer to timing table		
CVBS:	480i		
	3840x2160		
EMBEDDED OS	A		
Embedded OS: USB SUPPORTED FILE FORM	Android 7		
USB SUPPORTED FILE FORMAT:	Picture - BMP, JPEG, PNG Video - Codec: MPEG1, MPEG2, MPEG2-PS, MPEG4, MKV Container: MPG, MP4, MOV, VOB, DAT, MKV Audio - Codec: AAC, HEAAC, MPEG1,		
	MPEG2 Container: AAC, M4A, MP3		